

Frame Paspoort: Kanzo Adventure 7E7



1. General info

Brand	Ridley
Model	Kanzo Adventure
First intro (modelyear?)	2022
Description (intended use of frame)	Gravel-Bikepacking

2. Material

Frame material	High Modulus Elitel Carbon
----------------	----------------------------

3. Weight

Frame	gr.
XS	1260
S	1290
M	1310
L	1360
XL	1390
Weight fork	415

4. Cableparts

Mechanical 1x

Article code	Description	Quantity	Position on frame
FRPGRORID011	Closed plug - Slot 17x8	1	Head tube left
FRPGROJAG010	Jagwire Mechanical grommet flat top	1	Rear dropout
CABFOAJAG001	Jagwire NBR Foam Tube 5,5mm inner/8,2mm outer	0,5	Down tube
CABFOAJAG001	Jagwire NBR Foam Tube 5,5mm inner/8,2mm outer	0,5	Down tube

DI2 1x

Article code	Description	Quantity	Position on frame
FRPGRORID011	Closed plug - Slot 17x8	1	Head tube left
FRPGRORID007	Rear dropout plug	1	Rear dropout
CABFOAJAG001	Jagwire NBR Foam Tube 5,5mm inner/8,2mm outer	0,5	Down tube
SPTDI24ZA004	4ZA Di2 Int Bat Adap 27,2 SEP	1	Seatpost

ETAP

Article code	Description	Quantity	Position on frame
FRPGRORID011	Closed plug - Slot 17x8	1	Head tube left
FRPGROJAG002	Jagwire closed grommet 8mm	1	Rear dropout
CABFOAJAG001	Jagwire NBR Foam Tube 5,5mm inner/8,2mm outer	0,5	Down tube

5. Parts

Fork

Material	carbon
Fork length Axl to crown	400mm
Steerer tube length	300mm
Bearings	Upper: 11/8" Lower: 11/2"
Rake	50mm
OLD (Over Lock Distance)	100mm
Wheel axle diameter front	12mm
Thru-axle article code	QRE124ZA038
Length thru-axle	120mm
Pitch thru-axle	1,5mm
Suspension	Suspension ready frame geometry
Maximum tyre size	29 x 2,1"
Maximum tyre size mudguards	42mm
Fork crown plate for using front light	FOPG544ZA001
Fork crown rubber cover for front light	FOPG544ZA002
Maximum load using upper 2 mounts	1kg
Maximum load using cargo cage	3kg / forkleg
Maximum load using lowrider	9kg in total

Brakes

Disc brakes	YES
Disc brake Type	Flatmount, 20mm mount Max 160mm rotor

Frame & Wheels

Wheel dimension	700C
Build-in width	142mm
Wheel axle diameter rear	12mm
Wheel axle diameter front	12mm
Thru-axle article code Front / Rear	FR: QRET124ZA038 / RR: QRET124ZA039
Integrated Dual cable guid down tube	FRPSTORID023
Top tube frame cover	FRPTTCRID001
Top tube frame cover - T-bone	FRPTTCRID002

6. Geometry

	A	B	C	C'	D	E	F	G	H	I	J	S	R
XXS	-	-	-	-	-	-	-	-	-	-	-	-	-
XS	760	470	530	-	115	74,5	70,8	435	75	1024	/	546	379
S	785	495	550	-	140	74,0	70,8	435	75	1041	/	569	387
M	810	520	570	-	165	74,0	70,5	435	75	1065	/	591	401
L	835	545	592	-	192	74,0	70,5	435	75	1088	/	617	415
XL	860	570	615	-	215	73,5	70,5	435	75	1107	/	639	426

Headset

Headset diameter	Upper: 1 1/8" Lower: 1 1/2"
International Headset code	IS242/28,6 IS52/40
Headset description	FSA HSE Race CNC-FC2 alloy cap
Headset article code	HSERACFSA008
Maximum amount of spacers	40mm

Seatpost

Seatpost diameter	27,2mm round
Seatpost clamp description	Integrated Seatpost Clamp for 27,2mm Seatpost - M6
Seatpost clamp article code	SPCINT4ZA003
Maximum torq setting seatpost clamp	10Nm
Seatpost cover article number	FRPSEPNOB002

Bottom Bracket

Bottom bracket description	BB86
Diameter	41mm
Width	86,5

Drive train

Maximum chain ring	N/A
Hanger description	AMP: Hanger set NFD HXD HAARCERID041

Compatible groupsets

Shimano 1x groupsets
Sram 1x groupsets
Campagnolo 1x groupset

